Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Quality Engineering Test Report

SERIES: SCW03A 3W DC-DC SINGLE OUTPUT CONVERTER

SAMPLE: **A:SCW03A-05 +5V / 600mA**
B:SCW03A-12 +12V/250mA
C:SCW03A-15 +15V/200mA

NO	TEST ITEM	TEST CONDITION / SPECIFICATION	RESULT	VERDICT
1	DC INPUT VOLTAGE RANGE	I/P:TESTING SPEC: 9~18VDC O/P:FULL LOAD	A:5.7~18VDC	P
2	LINE REGULATION	I/P: 9~18VDC SPEC: 0.5% MAX O/P: FULL LOAD	A:-0%~+0.1% B:-0%~+0.1% C:-0%~+0%	P
3	LOAD REGULATION	I/P: 12VDC SPEC: ±1% O/P:MIN. TO FULL LOAD	A:-0.2%~+0% B:-0%~+0.1% C:-0.04%~+0.06%	P
4	OUTPUT VOLTAGE TOLERANCE	I/P: 9~18VDC SPEC: NONE O/P:MIN. TO FULL LOAD	A:-0.2%~+0.1% B:-0.1%~+0.1% C:-0.04%~+0.06%	P
5	RIPPLE&NOISE	I/P: 12VDC SPEC: 100mV O/P:FULL LOAD	A:30mV B:20mV C:10mV	P
6	DC INPUT CURRENT	I/P: 12VDC SPEC: NONE O/P:FULL LOAD	A:0.32A	P
7	OVER LOAD PROTECTION	I/P: 12VDC SPEC: NONE O/P:TESTING	A:166% B:188% C:200%	P
8	O/P VOLTAGE ACCURACY	I/P: 12VDC SPEC: ±2% O/P:MIN. LOAD	A:+0.40% B:+0.17% C:+0%	P
9	SET UP TIME	I/P:12VDC SPEC: NONE O/P:FULL LOAD	A:2.04mS	P
10	HOLD UP TIME	I/P:12VDC SPEC: NONE O/P:FULL LOAD	A:0.2mS	P
11	EFFICIENCY	I/P: 12VDC SPEC: 73% O/P:FULL LOAD	A:78.4% B:80.7% C:83.3%	P
12	INSULATION RESISTANCE	SPEC:I/P--O/P 500VDC/100M Ohms MIN.	A:I/P--O/P >100M Ohms	P
13	DIELECTRIC / WITHSTAND VOLTAGE	SPEC: I/P-- O/P: 1000VDC/ 1 min (10mA CUT-OFF)	A:NO BREAK I/P--O/P :<0.02mA	P
14	BURN-IN TEST	I/P:12VDC O/P:FULL LOAD TA:25 °C BURN-IN DURATION : 4 hrs	A:NO BREAK B:NO BREAK C:NO BREAK	P

NEXT

<table>
<tr><th>NO</th><th>TEST ITEM</th><th>TEST CONDITION / SPECIFICATION</th><th>RESULT</th><th>VERDICT</th></tr>
<tr><td>15</td><td>TEMPERATURE RISE
TEST T rise OF PARTS</td><td>A:I/P :12VDC AFTER 4 hrs BURN-IN
O/P :FULL LOAD TA:25℃
<table>
<tr><th>POSITION</th><th>SAMPLE</th><th>TEMP</th><th>T rise</th></tr>
<tr><td>CASE</td><td>SCW03A-05</td><td>37.0℃</td><td>12.0℃</td></tr>
</table></td><td></td><td>P</td></tr>
<tr><td>16</td><td>CONSTRUCTION
INSPECTION
(FOR QC INSPECTION
REFERENCE ONLY)</td><td colspan="3">1. PACKING : 軌道型塑膠加紙盒包裝
2. MARKING : MODEL
3. MECHANICAL : SIX-SIDED SHIELD METAL CASE
4. DIMENSIONS : WXHXD=31.8X12.2X20.3mm, PIN :0.5∅x3.8mm</td></tr>
</table>

DATE	SAMPLE	TEST RESULT	TEST	APPROVAL
1998.08.15	SCW03A-05	PASS	T.K.CHENG	MAX LIN
1999.01.28	SCW03A-12 SCW03A-15	PASS	T.K.CHENG	MAX LIN

PREVIOUS